



ON-DEMAND, ON-SITE, ON-TIME.



DUST SPRAY CANNON

A HISTORY OF INNOVATION



The Dust Spray Cannon is an independent dust control unit equipped with a fog cannon installed on a manual telescopic mast, a plastic water tank, a power generating set and an optional road trailer. A perfect solution for small to medium sized working areas where water and energy are not available.

STANDARD SPECIFICATIONS:

Electrical engine power (fan)	2,2 kW
Coverage (*without wind)	20 m
Generating set	
with diesel engine	3,7 kW 230 V – Yanmar L70N
Fuel tank capacity	18 litres
Water tank capacity	1000 litres
Water consumption	6,25 l/min
Lifting system	Manual
Manual tilting system	 -30°/+10°
Running time	160 min
Water inlet filter	170 µ
Working angle	 335°
Dim. on base	
(LxWxH min/max)	2374 x 1210 x 1990/3920 mm
Dim. on road trailer	
(LxWxH min/max)	3780 x 2015 x 2540/4470 mm
Dry weight on base/on road trailer	490/840 kg

KEY FEATURES:

- Coverage: 20 meters
- Water consumption: 6,25 l/min
- Integrated generator: 3,7 kW
- Integrated water tank: 1000 liters
- Optional road trailer

TYPICAL APPLICATIONS INCLUDE:

- Mining
- Demolition

STANDARD EQUIPMENT

- Telescopic vertical mast (max. height: 4m)
- 1000 litres water tank
- 3,7 kW – 230 V integrated generating set
- Integrated control panel
- Stainless steel crown with nozzles
- Nebulizer cannon (foldable for transport)
- Telescopic mast with double crank winch
- Water Supply and Main Electricity network connections
- High pressure washer connection
- Water draining system
- Structure on base with forklift pockets for easy handling
- command switches
- circuit breakers
- emergency stop button

