

Garic Enviro Wheel Wash 14

The Enviro Wheel Wash 14 has been designed with small, low volume traffic and 'nospace' projects in mind. The unit also lends itself to urban-developments where space is a premium, muck is a problem, and where traditional wheel wash solutions simply cannot fit.

This unit can be quickly deployed without the need for movement orders and be delivered to site with the minimum of fuss. This unit is the smallest powered spray wash in our range. A 25mm water supply is required to give the unit its initial fill. This also maintains the water level within the unit. Water waste is minimized as it is recirculated from the containing sump. As wheels pass through the unit, the rumble bars agitate the tyre treads and they are cleaned by high pressure horizontal spray jets. This ensures more than a 360 degree clean of standard tipper lorry tyres. Travelling very slowly through the unit achieves a clean similar to our much larger units.

This unit is especially designed for 8 wheel tipper lorries, which don't have under run bars.



Key Features:

- Powered compact wash with small footprint
- Steel heavy duty fabrication
- Surface mounted no need for digging
- Automatic sensor (magic eye)
- Horizontal spray jets
- Heavy duty lifting and lashing points
- Ball cock water fill system
- Galvanised ramps
- Low angle entry and exit
- 3.7Kw soft start water pump (per bay)







Garic Enviro Wheel Wash 14



Standard Specifications:

Product code

300003

Dimensions with ramps LxWxH

8657mm x 4578mm x 1805mm

Dimensions without ramps LxWxH

2500mm x 4578mm x 1805mm

Weight without ramps

4585kg

Weight with ramps

6500kg

Weight of the ramps

478kg Each

Power type

Requires external generator

Heavy duty lifting lashing points

Included

Powered wash 3-7kw soft start pump

Included

Direction signs

Included

Optional extra available

- Generator 3 Phase 20 KVA
- Water Bowser



Previously named City Wheel Wash

